

elemelt



Hot Melt Stick & Applicator Catalog






Elemelt, an Ellsworth Adhesives brand, offers a range of both stick and bulk hot melt adhesives and specialty cleaning products in various formats to meet your product assembly and packaging needs. Available formulas include EVAs, acrylics, polyamides, metallocenes, and more. Elemelt purge cleaning compounds are safe, non-hazardous, and help flush and clean thermoplastics and PSAs from bulk reservoir tanks, or reactive PUR hot melts from equipment.

Ellsworth Adhesives is a global corporation specializing in the distribution of specialty chemicals and equipment, distributing a wide range of hot melts, adhesives, sealants, lubricants, coatings, encapsulants, tapes, soldering products, surface preparations, specialty chemicals, maintenance, and repair products and dispensing equipment. Ellsworth Adhesives not only offers an extensive product line, but is the only integrator specializing in the supply and logistics of specialty chemicals.

To place an order or for more information, please contact an Ellsworth Adhesives representative at I (800) 888-0698 or email info@ellsworth.com.



Elemelt Hot Melt Stick Guide

| Elemelt | Description & Application | Color / Chemistry | Appl. Temp (°F) | Open Time (sec) | Sizes |
|---------|---|----------------------------------|-----------------------|-----------------------|---|
| HMS425 | APAO with a long open time for bonding foam to foam, foam to fabric, and other porous substrates. Can be extruded or sprayed. | Off-White / APAO | 350 - 375 | 3 - 7 minutes | ½" x 10" 5%" x 15" |
| HMS600 | General purpose. Bonds many woods & wood composites for woodworking & cabinetry. | Amber / EVA | 350 - 400 | 40 - 50 | ½" x 10" or 15" |
| HMS601 | Low melt for packaging & carton sealing. Bonds to most porous materials. | Tan / EVA | 250 - 300 | 5 | ½" x 10" or 15" 5/8" x 10" 5/8" x 8" Quad |
| HMS701 | Fast set for corrugated carton sealing. Low temperature resistance. Bonds most porous materials (wood, paper, cloth). | Amber / EVA | 250 - 380 | 15 | ½" x 10" or 15" 5%" x 10" 1¾" x 1¾" 5%" x 8" Quad 1" x 3" |
| HMS702 | Fast set for corrugated carton sealing & small packaging. Good adhesion to some corrugated packaging & paper products. | Amber / EVA | 250 - 380 | 5 | ½" x 10" or 15" |
| HMS707 | High performance for difficult substrates (porous or non-porous). Bonds glass, leather, metals, magnets, ceramics, wood, ABS, PVC, & some vinyls. | Clear or Black / EVA | 380 | 30 | ½" x 10" or 15" 5/8" x 10" |
| HMS711 | Excellent hot tack, fast set packaging. Good adhesion to plain & some corrugated packaging. | Tan / EVA | 380 | 5 - 10 | ½" x 10" or 15" %" x 10" 1" x 3" |
| HMS735 | High strength for metal, plastics & non-porous substrates. Bonds leather, wood, ceramic, & non-porous materials. | Amber / EVA | 325 - 380 | 25 | ½" × 10" or 15" 5%" × 10" 1" × 3" |
| HMS739 | High strength wood bonder & dent remover. Bonds metals, plastics, ceramics, & non-porous materials. | Amber / EVA | 325 - 380 | 25 | ½" x 10" or 15" |
| HMS748 | Polyamide bonder for most plastics & woods (high temperatures) & paper, fabric, & ribbons (low temperatures). Resistant to oils, transmission fluids, brake fluid, & fuels. | Amber or Black / Polyamide | 275 - 380 | 15 | ½" x 10" or 15" |
| HMS800 | General purpose with excellent hot tack for packaging. Strong bonds to most papers & other porous materials. | Translucent / EVA | 350 - 400 | 25 - 35 | ½" x 10" or 15" |
| HMS900 | General purpose for assembly of plastics & woods at high temperatures. Bonds to porous & non-porous materials at low temperatures. | Clear / EVA | 250 - 380 | 60 | ½" x 10" or 15" 5/8" x 8" Quad I" x 3" |
| HMS925 | High performance acrylic with long open time. Makes flexible bonds on hard-to-bond substrates like concrete, metal, wood, vinyl, glass, and ceramic. | Clear / Acrylic | 350 - 390 | 60 | ½" x 10" |

Stick & Applicator Reference Chart

| Hot Melts | | | Applicators | | |
|-------------------|-------------------------------------|-------------------------------------|-------------------------------------|-----------------------------------|-----------------------------------|
| ½" x 10" or 15" | Ellsworth Adhesives EA100-12 | Power Adhesives 806-12 | Fastenmaster HB220 | Surebonder Pro9700A | 3M AE II |
| | | | | | |
| 5/8" x 10" or 15" | Ellsworth Adhesives EA100-58 | Surebonder Pro2-500 | Power Adhesives 806-15 | Power Adhesives 820-15 | |
| I" x 3" | 3M PG II Applicator | | | | |
| 13/4" x 13/4" | Power Adhesives Tec 3400 Extrude | Power Adhesives Tec 6100 Extrude | Power Adhesives Tec 7100 Extrude | Power Adhesives Tec 6300 Spray | Power Adhesives Tec 7300 Spray |
| 5%" x 8" Quad | 3M EC Applicator | 3M TC w/Quadrack | | | |



Compatible Nozzle Chart

| Nozzle | Nozzle Diameter / Outlet mm/inch (ID) | Nozzle Length mm/inch | Thread Size (inch) | Description |
|---------------------------|--|--------------------------|----------------------------------|---|
| Power Adhesives ADJ012 | 6.0 / 2.3 wide | 30 / 1.2 | ⅓ ₁₆ UNF | Ball Valve Steel / Ribbon Extension Copper Nozzle |
| Power Adhesives ADJ013 | 3.0 / .11 orifice | 30 / 1.2 | ⁷ ∕ ₁₆ UNF | Ball Valve Steel / Angled Extension Copper Nozzle |
| Power Adhesives ADJ014 | 1.25 / .049 orifice | 30 / 1.2 | ⁷ ∕ ₁₆ UNF | Ball Valve Steel / Precision Extension Copper Nozzle |
| Power Adhesives ADJ023 | 3.5 / .13 orifice | 15 / .60 | 7∕16 UNF | Ball Valve Steel Hub / Standard Aluminum Nozzle |
| Power Adhesives ANZ016 | 2.0 / .13 orifice | 15 / .60 | 7∕16 UNF | Ball Valve Steel Hub / Standard Aluminum Nozzle |
| Power Adhesives ADJ010 | 2.0 / .08 orifice | 12 / .47 | ⅓ ₁₆ UNF | Ball Valve / Standard Aluminum Nozzle |
| Power Adhesives MDJ016 | 2.0 / .08 orifice | 12 / .47 | ⅓ ₁₆ UNF | Oiler Valve / Standard Aluminum Nozzle |
| Power Adhesives MDJ018 | 1.25 / .05 orifice | 5 / .20 | ⅓ ₁₆ UNF | Oiler Valve / Standard Aluminum Nozzle with Copper Tip |
| Power Adhesives MDJ019 | 5.0 / .08 width | 12 / .47 | ⅓ ₁₆ UNF | Oiler Valve / Short Aluminum Nozzle with Copper Ribbon Tip |
| Power Adhesives MDJ021 | 2.0 / .08 orifice | 19 / .74 | ⁷ ∕16 UNF | Ball Valve / Standard Aluminum Extension Nozzle |

Compatible Nozzle Chart

| Nozzle | Nozzle Diameter / Outlet mm/inch (ID) | Nozzle Length mm/inch | Thread Size (inch) | Description |
|-----------------------------|--|---|---|--|
| FastenMaster PA-10-SPN28 | 2.0 / .07 orifice | 57 / 2.2 | ⁷ ∕ ₁₆ UNF | Ball Valve Steel Hub / Angled Injection Steel Nozzle |
| Surebonder MNR-23 | 3.0 / .11 orifice | 45 / 1.7 | ⅓ ₁₆ UNF | Ball Valve Steel / Standard Extended Steel Nozzle |
| Surebonder MNR-21 | 3.0 / .11 orifice | 38 / 1.5 | 7∕16 UNF | Ball Valve Steel / Standard Short Steel Nozzle |
| Surebonder 101 Valve | N/A | N/A | ⅓ ₁₆ UNF | Brass Check Valve (Required for 103N, 103R & 103F Nozzles) |
| Surebonder 103N | 2.0 / .08 orifice | 36 / 1.4 | ⁵ / ₁₆ - 24 UNF | Aluminum Hub / Brass Blunt Extension Nozzle (Requires 101 Valve) |
| Surebonder 103R | 3.1 / .125 orifice | 45 / 1.7 | ⁵ / ₁₆ - 24 UNF | Steel Hub / Brass Angled Extension Nozzle (Requires 101 Valve) |
| Surebonder 103F | 1.3 / .05 width | 45 / 1.7 | ⁵ / ₁₆ - 24 UNF | Steel Hub / Brass Ribbon Extension Nozzle (Requires 101 Valve) |
| 3M 9234 KIT w/ 992 I | 9921 Nozzle / 2.2 / .09 orifice | Nozzle 18.5 / .73 Nozzle w/Valve 33 / 1.3 | ⁷ / ₁₆ UNF/ ⁷ / ₁₆ UNF | Aluminum Check Valve w/ Steel Fluted Nozzle (For use with 3M EC & TC applicators) |
| 3M 9729 KIT w/ 9940 | 9940 Nozzle / 3.1 / .125 orifice | Nozzle 18.5 / .73 Nozzle w/Valve 66 / 2.6 | 7/ ₁₆ UNF/ 33/ ₆₄ - 20 UNF | Brass / Aluminum Check Valve w/ Steel Fluted Nozzle (For use with 3M PG II applicator) |
| 3M 9785 | 1.7 / .07 orifice | 32.5 / 1.27 | ⅓ ₁₆ UNF | Tapered Aluminum Nozzle |
| 3M 9946 | 1.8 / .072 orifice | 44.5 / 1.7 | ⅓ ₁₆ UNF | Brass Nozzle |



W129 N10825 Washington Drive, Germantown, WI 53022 I (800) 888-0698 | ellsworth.com info@ellsworth.com