

EA-200 BULK HOT MELT APPLICATOR



SPECIFICATIONS

- Power supply: 120 V / 60 Hz
- Power consumption: 500 W
- Temperature control: Thermostat
- Operating temperature: 20 - 200 °C / 70 - 390 °F
- Temperature consistency: + - 5 °C
- Heat-up time: Approx. 5 min
- Gross tank capacity: 250 mL / 8.4 oz
- Conveying system: Mechanical
- Weight: 2.7 lbs

The EA-200 all-electric bulk hot melt dispense tool does not require compressed air to operate. The large hot melt chamber opening makes filling easy with a 250 mL (8.4 oz) capacity, reducing spillage. Its well-designed shape and adjustable trigger provide a comfortable dispense experience. It also features a magnetic foot at the bottom of the base, which helps prevent the tool from tipping over on a magnetic worktable. On non-magnetic surfaces, the wire stand at the front of the tool provides added security.

FEATURES

- Single thermostat that controls all temperature settings up to 200 °C / 390 °F
- Designed for dispensing bulk adhesives like pellets, pillows, granules, and 43 mm (1 ¾") slugs
- Can be arranged over a work bench or on an assembly line by attaching the eyehook to a retractable tool balancer (sold separately)
- Drip-free dispensing nozzle
- Temperature adjustable using a 3/16" screwdriver



W129 N10825 Washington Drive
Germantown, WI 53022
877.454.9224 | ellsworth.com