

Alodine®

Alodine® 1132™ Touch-N-Prep® Coating



Henkel



e ELLSWORTH
ADHESIVES

Global Distributor of Henkel LOCTITE
(800) 888-0698 info@ellsworth.com



Alodine® 1132™ Touch-N-Prep® No-Rinse Conversion Coating

	Metal Processing Lines	Aircraft Depaint & Repaint	Coolants	Henkel Product Number <small>Case</small>	Consistency	Form	How to Apply	Mix Ratio (product:water)	Chemistry	Aluminum	Temperature	Time	
Chemical Specialties	Application			Characteristics					Substrate	Operation		Description	
Alodine® 1132™ Touch-N-Prep® Coating	•	•	•	592939	Liquid	Ready-to-Use	Pen	Use as Received	Chromate	•	Ambient	Until Dry	Alodine® 1132™ Touch-N-Prep® Coating is a felt-tipped pen that provides a chromate conversion coating on aluminum surfaces prior to painting. Meets MIL-DTL-81706B, Class 1A & 3, Form VI, Method D. Ideal for coating repair work.
Alodine® Touch-N-Prep® Replacement Tips				598819	n/a	n/a	n/a	n/a	n/a		n/a	n/a	A felt replacement tip for use with the Alodine® Touch-N-Prep® coating applicator.



Touch-N-Prep® Coatings Pen

Henkel developed Alodine® 1132™ coating with the convenient Touch-N-Prep® applicator pen to provide a clean, easy-to-use method of repairing conversion coatings on aircraft and aircraft part surfaces.

The unique Alodine® 1132™ Touch-N-Prep® no-rinse conversion coating effectively repairs bare aluminum substrates to prevent corrosion. It does not require rinsing, and can be air-dried or force-dried with hot air.

The high-density acrylic tip of the Touch-N-Prep® pen can be modified with a single-edge razor blade to form any shape. The design of the Touch-N-Prep® pen allows repair of hard-to-reach places or the underside of aircraft. This new application method controls the amount of coating applied to the surface. Use Alodine® 1132™ Touch-N-Prep® sparingly – a little goes a long way. This optimized application method greatly reduces the amount of chemical used and generates no secondary waste associated with other repair methods.


Touch-N-Prep® coatings represent a dramatic environmental improvement over current methods of chemical coatings touch up. The easy-to-use, dry-in-place coating is a cost-effective and safe method of touch-up repairs of aircraft and aircraft part surfaces.


Product Features and Benefits


- Easy to use, cost effective touch-up and repair applicator
- Designed to save labor, material, and time with easy to use applicator
- Non-rinsing, dry-in-place technology
- Excellent paint adhesion and painted corrosion resistance
- Contains sufficient solution to treat up to 50 sq ft (4.6 sq m)


Pen Instructions

Touch-N-Prep® pens are designed for easy and safe repair of clean, bare, or previously painted aluminum surfaces. It is a non-rinse, dry-in-place application that can be applied using the following steps:


- 1.**  Before applying the coating, the treated surface must be cleaned using the following process:
- Use a moistened abrasive pad to remove oxides from the surface of the metal.
 - Wipe substrate with a damp lint-free cloth to ensure complete removal of soils and dislodged oxides generated from the previous step.
 - Allow surface to dry before Touch-N-Prep® application.

- 2.**  To activate, hold the Touch-N-Prep® pen upright, pop off the cap and hold the pen tip down onto a clean surface to begin the flow of solution to the tip. Do not twist or turn to remove the cap, since this may result in the pen leaking.

- 3.**  Press the pen tip down on the surface until solution fills the pen tip. Apply the Alodine® 1132™ solution to the metal surface with firm, smooth, even strokes, covering all edges. Overlap each stroke and allow to dry.

- 4.**  Within 5 minutes of the first coat, apply a second coat at a 90° angle to the first coat with the same smooth, firm stroke.

- 5.**  **AIR DRY**
Allow the Alodine® Touch-N-Prep® coating to air dry thoroughly.

- 6.**  Frequent short jabs to rewet the application tip are preferred to maintain constant coating weights and avoid over-wetting the felt tip.

- 7.**  Always immediately replace the cap when not in use to avoid evaporation and contamination.





Henkel – Your worldwide partner

NORTH AMERICA

Henkel Corporation

Aerospace
P. O. Box 312
2850 Willow Pass Road
Bay Point, CA 94565
USA
Tel: 925.458.8000
Fax: 925.458.8030

Henkel Corporation

Aerospace
32100 Stephenson Hwy.
Madison Heights, MI 48071
USA
Tel: 866.332.7024
Fax: 248.585.2896

Henkel Canada Corporation

Aerospace
2225 Meadowpine Blvd.
Mississauga, Ontario
Canada L5N 7P2
Tel: 905.814.6511
Fax: 905.814.6522

Henkel Corporation

For additional information:

866.332.7024

visit www.henkelna.com/aerospace

EUROPE

Henkel France

Aerospace
82, rue de Maubec
31300 Toulouse
France
Tel: +33.5.34.36.40.60
Fax: +33.5.34.36.40.69

Henkel France

Aerospace
Buroparc-Batiment B,
3 Allée Emile Reynaud
F-77200 Torcy
Tel: +33.1.6017.0202
Fax: +33.1.6017.3291

Henkel Netherlands

Aerospace
Henkel Nederland B.V.
Brugwal 11
3432 NZ Nieuwegein
The Netherlands
Tel: +31.30.6073.911
Fax: +31.30.6054.457

Henkel Oberflächentechnik GmbH - Germany

Henkelstraße 67
D-40589 Düsseldorf
Tel: +49.211.797.0
Fax: +49.211.798.0

Henkel Central Eastern Europe GmbH – Austria

Erdbergstraße 29
A-1030 Wien
Tel: +43.1.711.040
Fax: +43.1.71104.2534

ASIA

Henkel Singapore Pte. Ltd.

19 Jurong Port Road
Singapore 619093
Tel: +65.6266.0100
Fax: +65.6266.1161

Henkel Asia-Pacific & China Headquarters

No.928 Zhang Heng Road
Zhangjiang Hi-Tech Park, Pudong
Shanghai 201203
P. R. China
Tel: +86.21.2891.8000
Fax: +86.21.6100.6059

Approvals

**MIL-DTL-81706B, Type 1, Class
1A & 3, Form VI, Method D**

Boeing

Boeing (McDonnell Douglas)

Bombardier

Cessna

Dassault Aviation

Honeywell