

Material Application Guide

FREKOTE® BRAND MOLD RELEASE AGENT	POLYMER										COMPOUND							PROCESS											
	Epoxy (Non Gel-Coat)	Polyester Gel-Coat – Glossy	Polyester Gel-Coat – Matte	Polyester Gel-Coat / Resin – Low Shrink	Polyamide (PA / Nylon)	Polyester (Non Gel-Coat)	Polyethylene (PE)	Polypropylene (PP)	Vinyl Ester	Cast Polyurethane	Polymer Concrete	Butyl	EPDM	HNBR	Natural	Neoprene	Nitrile	Silicone	Thermoplastic Urethane (TPU)	Vamac	Viton	Cast Polymer / Solid Surface	Compression / Transfer / Vacuum Bagging	Filament Winding	Hand Lay Up / Spray Up	Injection Molding	Rotational Molding	Rubber-to-Metal Bonding	Tire Treads

KEY:
 ○ Highly Recommended
 ◆ Recommended

1450™	◆				◆	◆																◆	◆	◆						
1711™	◆				◆	◆																◆	◆	◆						
44-NC™	○		○		○	◆	◆	◆	◆													◆	○		◆					
55-NC™	○		◆	◆	◆	◆	◆	◆	◆													◆	○		◆					
700-NC™	○	◆		○	◆	○	◆	◆	○													◆	○	◆	◆					
710-LV™	○	◆		○	◆	○	◆	◆	○													◆	○	◆	◆					
720-NC™	○		◆	○	◆	○	○	○	○		○											◆	○	○	◆	○				
770-NC™	○	◆		○	◆	○	○	○	○													◆	○	○	◆		○			
800-NC™																													◆	
810-NC™																													◆	
815-NC™																													◆	
AC-4368™	◆				◆	◆																◆	◆	◆						
C-200™	○				○		○	○															○				○			
C-600™	○					◆			○																					
GMR™		○		◆																		○			○					
CUR™									○																					
EFR™	○		◆	○	◆	○	○	○	○													◆	○	○	◆	○				
EXITT™	◆				◆	◆																◆	◆	◆						
EXITT-EM™	◆				◆	◆																◆	◆	◆						
FREWAX®		◆																				◆			◆					
FRP-NC™		○		◆		◆																○			○					
HMT™	○		○		○	◆	◆	◆	◆													◆	○		◆					
HMT-2™	○		◆	◆	◆	◆	◆	◆	◆													◆	○		◆					
LIFFT™	◆				◆	◆																◆	◆	◆						
PUR-100™																		◆												
R-110™														○									○			◆		○		
R-120™											○	◆		○	◆	◆						○	○		◆		○			
R-150™											○	○	○	○	◆	◆	◆	○	○	◆		○	○		○		○	○	◆	
R-180™											○	○	○	○	◆	◆	◆	○	○	◆		○	○		○		○	○		
R-220™											○	○	○	○	◆	◆	◆	○	○	○										
RC-321™											○	○	○	○	◆	◆	◆	○	○	◆		○			○		○	○		
REL-EAZE™																														○
RIMLEASE 8™																										◆				
ROTOLEASE™							○	○																			○			
S-50™																	○						○		○		◆	◆		
SOLO®		○		◆																										
WOLO™		○		◆																		○			○					
WOLO-HL™				○																										

For technical product assistance, call 1.800.LOCTITE (562.8483) in the U.S., or 1.800.263.5043 in Canada.

www.henkelna.com/frekote



Visit the web for immediate access to:

- ✓ Distributor Information
- ✓ Technical Data Sheets
- ✓ Material Safety Data Sheets
- ✓ Product Literature